LiSHan

台州力山机械有限公司

TAIZHOU LISHAN MACHINERY CO., LTD.

地址: 浙江省台州市路桥区金清镇沙头工业区

Add: Shatou Village Industrial Park, Jinqing, Luqiao, Taizhou, Zhejiang

电话: 0086-15325655518 / 0086-15268880707

E-mail: sales1@chinalishan.com

http://www.chinalishan.com

LiSHan

台州力山机械有限公司

TAIZHOU LISHAN MACHINERY CO., LTD.

Drilling machine / Cut-off machine



THE QUALITY IS OUR ROOT, THE QUALITY IS OUR FUTURE

以质量取胜市场
用优质设备打造优质产品

Win the market by the quality
Makes the quality with the advanced equipment

LiSHan

台州力山机械有限公司
TAIZHOU LISHAN MACHINERY CO., LTD.

台州力山机械有限公司，坐落于风景秀丽的东海之滨，海陆空交通便捷。坐山望水，既古老又年轻的活力城市，如今被世人誉为：山海水城、和合圣地、制造之都——台州。

本公司是以专业制造型的生产企业，拥有自主研发及设计团队，并按德国、日本、台湾的工艺流程及操作标准制作，产品结构合理新颖而大方。主要出口到欧洲、美洲、中东、非洲、东南亚等国家和地区，赢得国内外中高端客户的信赖和赞美……

诚实、稳健、茁壮是企业发展的成长理念。永恒在于品质、品质营造未来，是我们企业的宗旨。

真诚欢迎国内外新老客户光临本公司，指导、洽谈、订购或来电查询，携手共创辉煌灿烂的明天！

Taizhou Lishan Machinery Co., Ltd. is located on the beautiful coast of the East China Sea, with convenient sea, land and air transportation. Sitting on mountains and looking for water is an old and young dynamic city, which is now known as Shanhai City, Hehe Holy Land and Taizhou, the capital of manufacture.

The company is a professional manufacturer with independent R&D and design team. It is manufactured according to the process and operation standards of Germany, Japan and Taiwan. The product structure is reasonable, novel and generous. Mainly exported to Europe, America, Middle East, Africa, Southeast Asia and other countries and regions, won the trust and praise of high-end customers at home and abroad...

Honesty, steadfastness and thriving are the growth concepts of enterprise development. Eternity lies in quality and quality to build the future, which is the purpose of our enterprise.

Sincerely welcome new and old customers at home and abroad to visit our company, guide, negotiate, order or inquire by telephone, and create a brilliant tomorrow hand in hand!

成就了一代代精品产品
Generation upon generation of masterpiece products of achievement











规范化的管理
高素质的科技人员
Standardized management
Professional technical personnel



齐全的硬件设备
流水线的生产模式
Complete hardware equipment
Assembly line production pattern



DRILLING MACHINE

钻床系列


铸件
◆ 厚重而结实的铸铁制造，铸铁经过回火失效加工处理，刚性更好
◆ 表面经过多道工序喷塑处理，外观更新颖
◆ 操作台面经过精加工制作，精度更高

刚件
◆ 主轴、齿轮轴、接杆经过硬度调质处理
◆ 手柄座组件采用钢件加工制作，耐磨性好，使用寿命长

电器
◆ 本机器前置开关，单独急停
◆ 护目镜结构比较稳重而结实
◆ 安全性能好，符合欧洲发达国家标准设计，产品新颖而大方，适合欧美国家的风格



钢管立柱
Steel column



45°旋角
45° Rotation



机头可升降
Raise and lower the head

Castings:
◆ Better rigidity due to construction by heavy solid cast Iron after tempering failure processing
◆ Excellent appearance due to surface treated by multi–process spray treatment
◆ High precision due to highly processed operating table surface

Steelworks:
◆ Good wearing quality and long performance life
◆ Harden and tempering treatment of Spindle,gear and arbor
◆ Steel–maded handle seat assembly

The Electrical parts:
◆ The machine is with front switch and the emergency stop
◆ Solid and secure safety guards
◆ Good safety performance in accordance with the European developed countries standard design novel and natural products suited to Europe and American style



Z1516A

详细参数 Detailed Parameters

型号 Model	Z1513A	Z1516A
功能: Feature	Drilling	Drilling
钻孔范围: Drill Capacity	13mm	16mm
夹头: Chuck Capacity	B16 1~13mm	B16 1~16mm
立柱直径: Column Diameter	70mm	70mm
主轴行程: Spindle Travel	85mm	85mm
旋径: Swing	360mm	360mm
主轴到工作台最大距离: Max. Distance spindle to table	/	335mm
主轴到底座最大距离: Max. Distance spindle to base	540mm	540mm
主轴锥度: Spindle Taper	B16	B16
转速范围: Speed Range	200~2400rpm	200~2400rpm
速度: No. of Speed	5	5
工作台尺寸: Table Size	/	267x230mm
底座尺寸: Base Size	490x310mm	490x310mm
机器总高: Overal Height	980mm	980mm
电机功率: Motor	550W/400V/50Hz	550W/400V/50Hz
重量: Weight	72Kg	78Kg
包装尺寸: Packing Size	1055x610x380mm	1055x610x380mm
20尺装柜量: Quantity for 20ft	114PCS	114PCS

Quality Efficiency Cost Effectiveness



Z1720A



▸护镜断电功能
Chuck Guard Micro Switch Assy



▸控制面板
Panel



Z2025A

详细参数 Detailed Parameters

型号 Model	Z1720A	Z2025A
功能: Feature	Drilling	Drilling
钻孔范围: Drill Capacity	20mm	25mm
夹头: Chuck Capacity	B16 1~16mm	B16 1~16mm
立柱直径: Column Diameter	70mm	85mm
主轴行程: Spindle Travel	100mm	135mm
旋径: Swing	410mm	510mm
主轴到工作台最大距离: Max. Distance spindle to table	320mm	280mm
主轴到底座最大距离: Max. Distance spindle to base	530mm	540mm
主轴锥度: Spindle Taper	MT2	MT3
转速范围: Speed Range	200~2400rpm	200~2400rpm
速度: No. of Speed	5	5
工作台尺寸: Table Size	283x248mm	338x300mm
底座尺寸: Base Size	520x345mm	600x385mm
机器总高: Overal Height	1010mm	1100mm
电机功率: Motor	750W/400V/50Hz	1100W/400V/50Hz
重量: Weight	95Kg	144Kg
包装尺寸: Packing Size	1055x610x380mm	1595x710x485mm
20尺装柜量: Quantity for 20ft	114PCS	46PCS

DRILLING MACHINE

钻床系列









Z1516B

详细参数 Detailed Parameters

型号 Model	Z1516B
功能: Feature	Drilling
钻孔范围: Drill Capacity	16mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	70mm
主轴行程: Spindle Travel	85mm
旋径: Swing	360mm
主轴到工作台最大距离: Max. Distance spindle to table	335mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	B16
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	267x230mm
底座尺寸: Base Size	490x310mm
机器总高: Overal Height	980mm
电机功率: Motor	550W/400V/50Hz
重量: Weight	85Kg
包装尺寸: Packing Size	1055x610x380mm
20尺装柜量: Quantity for 20ft	114PCS

Quality Efficiency Cost Effectiveness



▸护镜断电功能
Chuck Guard Micro Switch Assy



▸控制面板
Panel

DRILLING MACHINE

钻床系列



Z1520F

详细参数 Detailed Parameters

型号 Model	Z1520F
功能: Feature	Drilling
钻孔范围: Drill Capacity	16mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	73mm
主轴行程: Spindle Travel	85mm
旋径: Swing	360mm
主轴到工作台最大距离: Max. Distance spindle to table	900mm
主轴到底座最大距离: Max. Distance spindle to base	1210mm
主轴锥度: Spindle Taper	B16
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	280x280mm
底座尺寸: Base Size	520x330mm
机器总高: Overal Height	1620mm
电机功率: Motor	550W/400V/50Hz
重量: Weight	90Kg
包装尺寸: Packing Size	1525x655x440mm
20尺装柜量: Quantity for 20ft	58PCS

DRILLING MACHINE

钻床系列





操作台面经过精磨加工制作
The work table is made by fine grinding



Z1720B

详细参数 Detailed Parameters

型号 Model	Z1720B
功能: Feature	Drilling
钻孔范围: Dril Capacity	20mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	70mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	320mm
主轴到底座最大距离: Max. Distance spindle to base	530mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	283x248mm
底座尺寸: Base Size	520x345mm
机器总高: Overal Height	1010mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	106Kg
包装尺寸: Packing Size	1055x610x380mm
20尺装柜量: Quantity for 20ft	114PCS

Quality Efficiency Cost Effectiveness





护镜断电功能
Chuck Guard Micro Switch Assy



Z1725F

DRILLING MACHINE

钻床系列

详细参数 Detailed Parameters

型号 Model	Z1725F
功能: Feature	Drilling
钻孔范围: Drill Capacity	25mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	80mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	850mm
主轴到底座最大距离: Max. Distance spindle to base	1160mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	320x320mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1630mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	128Kg
包装尺寸: Packing Size	1525x655x440mm
20尺装柜量: Quantity for 20ft	58PCS

DRILLING MACHINE

钻床系列





操作台面经过精磨加工制作
The work table is made by fine grinding



护镜断电功能
Chuck Guard Micro Switch Assy



Z2025B

详细参数 Detailed Parameters

型号 Model	Z2025B
功能: Feature	Drilling
钻孔范围: Drill Capacity	25mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	85mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	280mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	338x300mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1100mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	160Kg
包装尺寸: Packing Size	1595x710x485mm
20尺装柜量: Quantity for 20ft	46PCS

Quality Efficiency Cost Effectiveness



护镜断电功能
Chuck Guard Micro Switch Assy





DRILLING MACHINE

钻床系列

Z2032F

详细参数 Detailed Parameters

型号 Model	Z2032F
功能: Feature	Drilling
钻孔范围: Drill Capacity	32mm
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	98mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	860mm
主轴到底座最大距离: Max. Distance spindle to base	1200mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	410x380mm
底座尺寸: Base Size	650x440mm
机器总高: Overal Height	1770mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	237Kg
包装尺寸: Packing Size	1595x710x610mm
20尺装柜量: Quantity for 20ft	33PCS

DRILLING MACHINE


DRILLING & TAPPING

钻孔攻丝系列


铸件
◆ 厚重而结实的铸铁制造，铸铁经过回火失效加工处理，刚性更好
◆ 表面经过多道工序喷塑处理，外观更新颖
◆ 操作台面经过精加工制作，精度更高

刚件
◆ 主轴、齿轮轴、接杆经过硬度调质处理
◆ 手柄座组件采用钢件加工制作，耐磨性好，使用寿命长

电器
◆ 本机器前置开关，单独急停
◆ 护目镜结构比较稳重而结实
◆ 安全性能好，符合欧洲发达国家标准设计，产品新颖而大方，适合欧美国家的风格



钻攻两用
Drilling & Tapping



45°旋角
45° Rotation



机头可升降
Raise and lower the head

Castings:
◆ Better rigidity due to construction by heavy solid cast Iron after tempering failure processing
◆ Excellent appearance due to surface treated by multi-process spray treatment
◆ High precision due to highly processed operating table surface

Steelworks:
◆ Good wearing quality and long performance life
◆ Harden and tempering treatment of Spindle,gear and arbor
◆ Steel-maded handle seat assembly

The Electrical parts:
◆ The machine is with front switch and the emergency stop
◆ Solid and secure safety guards
◆ Good safety performance in accordance with the European developed countries standard design novel and natural products suited to Europe and American style



ZS1720B

详细参数 Detailed Parameters

型号 Model	ZS1720B
功能: Feature	Drilling & Tapping
钻孔范围: Drill Capacity	20mm
攻丝范围: Tapping Capacity	M12
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	70mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	320mm
主轴到底座最大距离: Max. Distance spindle to base	530mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	283x248mm
底座尺寸: Base Size	520x345mm
机器总高: Overal Height	1010mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	106Kg
包装尺寸: Packing Size	1055x610x380mm
20尺装柜量: Quantity for 20ft	114PCS

Quality Efficiency Cost Effectiveness



多楔带
Poly V-belt

磁性接近开关
Proximity switch



钻攻两用
Drilling & Tapping

DRILLING MACHINE

DRILLING & TAPPING

钻孔攻丝系列



ZS1725F

详细参数 Detailed Parameters

型号 Model	ZS1725F
功能: Feature	Drilling & Tapping
钻孔范围: Drill Capacity	25mm
攻丝范围: Tapping Capacity	M12
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	80mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	850mm
主轴到底座最大距离: Max. Distance spindle to base	1160mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	320x320mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1630mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	128Kg
包装尺寸: Packing Size	1525x655x440mm
20尺装柜量: Quantity for 20ft	58PCS

DRILLING MACHINE

DRILLING & TAPPING

钻孔攻丝系列





钻攻两用
Drilling & Tapping



ZS2025B

详细参数 Detailed Parameters

型号 Model	ZS2025B
功能: Feature	Drilling & Tapping
钻孔范围: Drill Capacity	25mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	85mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	280mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	338x300mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1100mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	160Kg
包装尺寸: Packing Size	1595x710x485mm
20尺装柜量: Quantity for 20ft	46PCS

Quality Efficiency Cost Effectiveness





操作台面经过精磨加工制作
The work table is made by fine grinding

DRILLING MACHINE

钻孔攻丝系列

DRILLING & TAPPING



ZS2032F

详细参数 Detailed Parameters


型号 Model	ZS2032F
功能: Feature	Drilling & Tapping
钻孔范围: Drill Capacity	32mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	98mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	860mm
主轴到底座最大距离: Max. Distance spindle to base	1200mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	410x380mm
底座尺寸: Base Size	650x440mm
机器总高: Overal Height	1770mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	237Kg
包装尺寸: Packing Size	1595x710x610mm
20尺装柜量: Quantity for 20ft	33PCS

DRILLING MACHINE

VARY-SPEEDING

无极变速系列

- 厚重而结实的铸铁制造
- 表面经过多道工序喷塑处理
- 变频二挡无极调速，面板带有数显装置
- 带有强制性反转功能
- 大功率6级电机



45°旋角
45° Rotation



机头可升降
Raise and lower the head

优点
刚性好，耐磨性强，精度高，功率大，外观新颖，适应当今时代产品转型升级，同时提高生产效率

- Construction by heavy solid cast Iron
- Surface treated by multi-process spray treatment
- Variable speeds with 2 steps,digital display in the panel
- With mandatory reversal function
- 6 pole motor

Advantages:
Better rigidity，Good wearing quality,High precision,Big power,Excellent appearance,
Adapt to the transformation and upgrade of products in modern times
Improve production efficiency

NEW



ZS1720B-VS

详细参数 Detailed Parameters

型号 Model	ZS1720B-VS
功能: Feature	Drilling Tapping & Mandatory reversal
无极变速功能: Variable speed function	yes
钻孔范围: Drill Capacity	20mm
攻丝范围: Tapping Capacity	M12
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	70mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	300mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	0~2100rpm
速度: No. of Speed	2
工作台尺寸: Table Size	283x248mm
底座尺寸: Base Size	520x345mm
机器总高: Overal Height	1010mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	107Kg
包装尺寸: Packing Size	1055x610x380mm
20尺装柜量: Quantity for 20ft	114PCS

Quality Efficiency Cost Effectiveness





钻攻两用
Drilling & Tapping

NEW



DRILLING MACHINE

无极变速系列

VARY-SPEEDING

ZS1725F-VS

详细参数 Detailed Parameters

型号 Model	ZS1725F-VS
功能: Feature	Drilling Tapping & Mandatory reversal
无极变速功能: Variable speed function	yes
钻孔范围: Drill Capacity	25mm
攻丝范围: Tapping Capacity	M12
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	80mm
主轴行程: Spindle Travel	100mm
旋径: Swing	410mm
主轴到工作台最大距离: Max. Distance spindle to table	850mm
主轴到底座最大距离: Max. Distance spindle to base	1160mm
主轴锥度: Spindle Taper	MT2
转速范围: Speed Range	0~2100rpm
速度: No. of Speed	2
工作台尺寸: Table Size	320x320mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1630mm
电机功率: Motor	750W/400V/50Hz
重量: Weight	129Kg
包装尺寸: Packing Size	1525x655x440mm
20尺装柜量: Quantity for 20ft	58PCS

DRILLING MACHINE

无极变速系列

VARY–SPEEDING





45°旋角
45° Rotation



机头可升降
Raise and lower the head



钻攻两用
Drilling & Tapping



磁性接近开关
Magnetic proximity switch

NEW



ZS2025B–VS

详细参数 Detailed Parameters

型号 Model	ZS2025B–VS
功能: Feature	Drilling Tapping & Mandatory reversal
无极变速功能: Variable speed function	yes
钻孔范围: Drill Capacity	25mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	85mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	280mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	0~2100rpm
速度: No. of Speed	2
工作台尺寸: Table Size	338x300mm
底座尺寸: Base Size	600x385mm
机器总高: Overal Height	1100mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	161Kg
包装尺寸: Packing Size	1595x710x485mm
20尺装柜量: Quantity for 20ft	46PCS

Quality Efficiency Cost Effectiveness



NEW



DRILLING MACHINE

无极变速系列

VARY–SPEEDING

ZS2032F–VS

详细参数 Detailed Parameters

型号 Model	ZS2032F–VS
功能: Feature	Drilling Tapping & Mandatory reversal
无极变速功能: Variable speed function	yes
钻孔范围: Drill Capacity	32mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	98mm
主轴行程: Spindle Travel	135mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	860mm
主轴到底座最大距离: Max. Distance spindle to base	1200mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	0~2100rpm
速度: No. of Speed	2
工作台尺寸: Table Size	410x380mm
底座尺寸: Base Size	650x440mm
机器总高: Overal Height	1770mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	238Kg
包装尺寸: Packing Size	1595x710x610mm
20尺装柜量: Quantity for 20ft	33PCS

DRILLING MACHINE

AUTOMATIC SERIES

自动钻床系列

SETUP 【设置–调节数显参数–设置】保持设置好的参数

【上下翻页数显参数】

【增减数显参数】

UP DOWN 【点动上下对刃】

DRILLING 【钻孔】

TAPPING 【攻丝】

复位 RESET 【回到原点】

启/停 ON/OFF 【操作系统启动/停止】

循环 CYCLE 【多次无限循环】

启动 START 【单次启动】

强制反转 REV 【攻丝卡机强制回退】

stop 【操作系统紧急断电】

NEW




ZK2025B

详细参数 Detailed Parameters

型号 Model	ZK2025B
功能: Feature	Drilling Tapping & Mandatory reversal
钻孔范围: Drill Capacity	25mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	85mm
主轴行程: Spindle Travel	110mm
旋径: Swing	510mm
主轴到底座最大距离: Max. Distance spindle to base	540mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
底座尺寸: Base Size	650x440mm
机器总高: Overal Height	1100mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	160Kg
包装尺寸: Packing Size	1595x710x485mm
20尺装柜量: Quantity for 20ft	46PCS

Quality Efficiency Cost Effectiveness



NEW



DRILLING MACHINE

自动钻床系列

AUTOMATIC SERIES

ZK2032F

详细参数 Detailed Parameters

型号 Model	ZK2032F
功能: Feature	Drilling Tapping & Mandatory reversal
钻孔范围: Drill Capacity	32mm
攻丝范围: Tapping Capacity	M16
夹头: Chuck Capacity	B16 1~16mm
立柱直径: Column Diameter	98mm
主轴行程: Spindle Travel	110mm
旋径: Swing	510mm
主轴到工作台最大距离: Max. Distance spindle to table	860mm
主轴到底座最大距离: Max. Distance spindle to base	1200mm
主轴锥度: Spindle Taper	MT3
转速范围: Speed Range	200~2400rpm
速度: No. of Speed	5
工作台尺寸: Table Size	410x380mm
底座尺寸: Base Size	650x440mm
机器总高: Overal Height	1770mm
电机功率: Motor	1100W/400V/50Hz
重量: Weight	250Kg
包装尺寸: Packing Size	1595x710x610mm
20尺装柜量: Quantity for 20ft	33PCS


DRILLING MACHINE

RB SERIES

RB系列



RB13



详细参数 Detailed Parameters

型号 Model	RB13	RB14
钻孔范围: Dril Capacity	13mm	13mm
夹头: Chuck Capacity	B16	B16
立柱直径: Column Diameter	48mm	48mm
主轴行程: Spindle Travel	50mm	50mm
旋径: Swing	210mm	210mm
主轴到工作台最大距离: Max. Distance spindle to table	260mm	315mm
主轴到底座最大距离: Max. Distance spindle to base	340mm	390mm
转速范围: Speed Range	390~3300rpm (6 speeds)	390~3300rpm (6 speeds)
工作台尺寸: Table Size	Φ170mm	Φ170mm
底座尺寸: Base Size	330x190mm	330x190mm
机器总高: Overal Height	610mm	668mm
LED灯：LED	NO	YES
十字激光灯: Cross laser	NO	YES
数显: Digital display	NO	NO
电机功率: Motor	300W/230V/50Hz	300W/230V/50Hz
毛净重: Weight	16Kg	17Kg
包装尺寸: Packing Size	490x365x250mm	530x370x260mm
20尺装柜量：Quantity for 20ft	660PCS	600PCS

NEW



RB14

Quality Efficiency Cost Effectiveness

NEW



RB16



NEW



RB18

详细参数 Detailed Parameters

型号 Model	RB16	RB18
钻孔范围: Dril Capacity	16mm	18mm
夹头: Chuck Capacity	B16	MT2
立柱直径: Column Diameter	58.5mm	58.5mm
主轴行程: Spindle Travel	50mm	50mm
旋径: Swing	230mm	230mm
主轴到工作台最大距离: Max. Distance spindle to table	300mm	300mm
主轴到底座最大距离: Max. Distance spindle to base	420mm	420mm
转速范围: Speed Range	400~2900rpm (12 speeds)	420~900/1200~2600rpm (Vary-speeding)
工作台尺寸: Table Size	Φ220mm	Φ220mm
底座尺寸: Base Size	440x250mm	440x250mm
机器总高: Overal Height	757mm	757mm
LED灯：LED	YES	YES
十字激光灯: Cross laser	NO	YES
数显: Digital display	NO	YES
电机功率: Motor	400W/230V/50Hz	400W/230V/50Hz
毛净重: Weight	30Kg	30.5Kg
包装尺寸: Packing Size	660x383x290mm	660x383x290mm
20尺装柜量：Quantity for 20ft	406PCS	406PCS

CUT-OFF MACHINE

切割机系列

MC4001

NEW



◆ 表面经过多道工序喷塑处理
◆ 操作台面精磨加工制作
◆ 高精度，高效率切削

◆ Surface treated by multi-process spray treatment
◆ Working table fine grinding and processing
◆ Cutting fast and accurately

详细参数 Detailed Parameters

型号 Model	MC4001
功率: Motor Power	2200W
电压: Voltage	230V/400V 50Hz
切割范围: Cutting Capacity	●30 ◎135 L110x10mm
转速: Spindle Speed	3000rpm
盘片直径: Diameter	16"ф400xф32/25.4x3.2mm
速度: Speed	520x306mm
毛净量: Weight	50Kg
包装尺寸: Packing size	710x610x450mm
20尺装柜量: Quantity for 20ft	144PCS



Quality Efficiency Cost Effectiveness

NEW

MC4002











◆ 表面经过多道工序喷塑处理
◆ 操作台面精磨加工制作
◆ 高精度，高效率切削

◆ Surface treated by multi-process spray treatment
◆ Working table fine grinding and processing
◆ Cutting fast and accurately

详细参数 Detailed Parameters

型号 Model	MC4002	MC4003
功率: Motor Power	3000W	4000W
电压: Voltage	400V 50Hz	400V 50Hz
切割范围: Cutting Capacity	●35 ◎140 L120x10mm	●40 ◎150 L115x10mm
转速: Spindle Speed	3000rpm	3000rpm
盘片直径: Diameter	16"ф400xф32/25.4x3.2mm	16"ф400xф32/25.4x3.2mm
速度: Speed	585x335mm	605x345mm
毛净量: Weight	58Kg	68Kg
包装尺寸: Packing size	710x610x450mm	710x610x450mm
20尺装柜量: Quantity for 20ft	144PCS	144PCS



MC4003

PLAIN VISE

平口钳系列

NEW



PV145H–5″

PV155H–6″



Quality Efficiency Cost Effectiveness



PV080–3″



PV110–4″



PV160–6″

详细参数 Detailed Parameters

型号 Model	PV080–3″	PV110–4″	PV160–6″	PV155H–6″	PV145H–5″
功能: Feature	Clamping	Clamping	Clamping	Clamping	Clamping
钳体总高: OverallHeight	60mm	60	95	110	110
钳体总长: Overal Lenth	210mm	230	320	490	410
钳体最大夹持: Max Clamping Capacity	80mm	110	160	155	145
钳口宽度: Jaw Width	80mm	106	160	160	125
钳口高度: Jaw Height	35mm	47	54	45	40
槽距: Slot Pitch	118mm	132	200	180	160
螺孔: Screw Hole	13mm	13	16	16	13
重量: Weight	3.7kgs	5.3kgs	14kgs	25.3kgs	15.2kgs